

FP560A

Manual L-sealer

(shown with T450 tunnel)



Modularity and excellent price/quality ratios are the main features characterizing the manual, semiautomatic and fully automatic sealers of the FP series. All the models of this range can indeed be supplied with or without shrink tunnel.

The INOX version machines are ideal to satisfy the exigencies of the food industry (meat, frozen food, fish, cheese, chocolate, etc.), and are characterized by a stainless steel frame (AISI 304) and the conveyor complying with the FDA, UE and USDA standards, concerning products in direct contact with food. Compared to the traditional L-sealing hood packers, the FP series provides higher outputs as well as the possibility of using Polyethylene film, besides the traditional shrink films, and includes different models for outputs ranging up to 3000 packs/hour.

Power supply	220 - 240 V
	1PH +N +PE
	50/60 Hz
Installed power	12 amp.
Sealing bar	22" x 17"
Maximum pack height	9"
Speed of conveyors	N/A
Speed up to	13 ppm *
Maximum size of film roll	31.50" x Ø 11.81"
Machine size	79.13" x 31.10"
	H 44.34"
Machine net weight	284.39 lbs.
Usable Films: Polyolefin and Polyethylene	Up to 120 gauge
<p>(*) Packs per minute. The stated speed can change according to the product size, the pack collation and the type of film used.</p>	

